

**SMP3E****Overview**

This power supply/charger converts a low voltage AC input into 6VDC, 12VDC or 24VDC @ 2.5 amp continuous supply current. This unit has a wide range of applications for access control, security and CCTV system accessories that require additional power.

Specifications**Input:**

- 6VDC or 12VDC output use TP1640 or 24VDC output use T2428100.

Output:

- 6VDC, 12VDC or 24VDC selectable output.
- 2.5 amp continuous supply current.
- Filtered and electronically regulated output.
- Short circuit and thermal overload protection.

Battery Backup:

- Built-in charger for sealed lead acid or gel type batteries.
- Automatic switch over to stand-by battery when AC fails.
- Maximum charge current 0.3 amp.
- Battery short circuit protection (circuit breaker).

Visual Indicators:

- AC input and DC output LED indicators.

Electrical:

- Operating temperature: -20° C to 49° C ambient.
- BTU/Hr.:
 - 6VDC: 5 BTU/Hr.
 - 12VDC: 10 BTU/Hr.
 - 24VDC: 18 BTU/Hr.
- System AC input VA requirement:
 - 6VDC/12VDC: 55.2VA.
 - 24VDC: 115VA.

Mechanical:

- Enclosure Dimensions (H x W x D approx.): 8.5" (215.9mm) x 7.5" (190.5mm) x 3.5" (88.9mm)
- Product weight (approx.): 2.8 lbs. (1.27 kg.).
- Shipping weight (approx.): 3.8 lbs. (1.72 kg.).

Features:

- Includes battery leads.
- Power supply/charger with enclosure.
- Fits one (1) 12VDC/7AH or two (2) 12VDC/4AH batteries.

Enclosure Dimensions (H x W x D) (approximate):
8.5" (215.9mm) x 7.5" (190.5mm) x 3.5" (88.9mm)

